



MATERIAL SAFETY DATA SHEET

Leisure Time Renew Tabs

1. Product And Company Identification

<p>Supplier Leisure Time 1400 Bluegrass Lakes Parkway Alpharetta, GA 30004 United States Telephone Number: (770) 521-5999 FAX Number: (770) 521-5959 Web Site: www.poolspacare.com</p>	<p>Manufacturer Advantis Technologies, Inc. 1400 Bluegrass Lakes Parkway Alpharetta, GA 30004 United States Telephone Number: (770) 521-5999 FAX Number: (770) 521-5959 Web Site: www.poolspacare.com</p>
<p>Supplier Emergency Contacts & Phone Number CHEMTREC - DAY OR NIGHT: (800) 424-9300</p>	<p>Manufacturer Emergency Contacts & Phone Number CHEMTREC - DAY OR NIGHT: (800) 424-9300</p>

Issue Date: 06/12/2006
 Product Name: Leisure Time Renew Tabs
 Chemical Name: Potassium Monopersulfate
 CAS Number: Not Established
 Chemical Family: Peroxygen Salt
 Chemical Formula: Proprietary
 MSDS Number: 318

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
BORIC ACID	10043-35-3	
MAGNESIUM CARBONATE	546-93-0	
POTASSIUMBISULFATE	7646-93-7	
POTASSIUMPEROXYDISULFATE	7727-21-1	
POTASSIUMPEROXYMONOSULFATE	10058-23-8	
POTASSIUMSULFATE	7778-80-5	
Sodium Carbonate	497-19-8	

Ingredients listed in this section have been determined to be hazardous as defined in 29CFR 1910.1200. Materials determined to be health hazards are listed if they comprise 1% or more of the composition. Materials identified as carcinogens are listed if they comprise 0.1% or more of the composition. Information on proprietary materials is available in 29CFR 1910.1200(i)(1).

EMERGENCY OVERVIEW

This product is a skin and eye corrosive, and a nose and throat irritant.

Hazards Identification (Pictograms)



3. Hazards Identification

No Data Available...

MATERIAL SAFETY DATA SHEET**Leisure Time Renew Tabs****3. Hazards Identification - Continued****Primary Routes(s) Of Entry**

Skin Contact

Eye Hazards

Corrosive to eyes. Eye contact may cause corrosion or ulceration. Severe eye damage may result if not immediately treated.

Skin Hazards

Corrosive to skin. Skin contact with aqueous solutions or the dry powder upon contact with moisture or perspiration may cause skin burns or ulceration; temporary body hair loss may occur in contacted areas. Skin contact with the product may cause allergic skin reactions in sensitive individuals.

Ingestion Hazards

May cause irritation of the throat. Ingestion may cause inflammation and damage to the lining of the stomach, resulting in bleeding. Ingestion may cause gastritis possibly progressing to necrosis or hemorrhage.

Inhalation Hazards

Inhalation may cause nose bleeds and irritation of the upper respiratory passages with coughing and discomfort.

Signs And Symptoms

Irritant to eyes and skin due to oxidizing properties

First Aid (Pictograms)**4. First Aid Measures****Eye**

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Call a physician or a poison control center immediately.

Skin

Wash affected areas with soap and water. Call a physician. Wash clothing before reuse.

Ingestion

DO NOT INDUCE VOMITING. Drink large amounts of water. Call a physician or a poison control center immediately.

Inhalation

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Consult Physician

Fire Fighting (Pictograms)**5. Fire Fighting Measures**

Flash Point: N/A °F

Fire And Explosion Hazards

Improper storage of large masses of this product can trap heat and lead to ignition of combustibles. Grinding or intensive mixing may cause decomposition with liberation of heat and oxygen; ignition of oxidizable material if present may occur.

MATERIAL SAFETY DATA SHEET**Leisure Time Renew Tabs****5. Fire Fighting Measures - Continued****Extinguishing Media**

In case of fire, soak (flood) with water.

Fire Fighting Instructions

Will release oxygen when heated, intensifying a fire. Firefighters should wear self-contained breathing apparatus and full protective gear.

GRINDING OR INTENSIVE MIXING MAY GENERATE SUFFICIENT HEAT TO FUSE PRODUCT AND CAUSE IGNITION OF OXIDIZABLE MATERIAL PRESENT.

6. Accidental Release Measures

Clean up spill immediately. Flush spill area with water in compliance with State and Federal Regulations.

Handling & Storage (Pictograms)**7. Handling And Storage****Handling And Storage Precautions**

Keep out of reach of children. Store material in a cool and dry place.

Handling Precautions

Avoid breathing dust or vapor. Avoid contact with skin and clothing. Avoid contact with eyes. Wash thoroughly after handling. Wash clothing after use.

Storage Precautions

Store in a cool dry place. Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Work/Hygienic Practices

Use safe chemical handling procedures suitable for the hazards presented by this material.

Protective Clothing (Pictograms)**8. Exposure Controls/Personal Protection****Engineering Controls**

Local exhaust acceptable. Special exhaust not required

Eye/Face Protection

Safety glasses with side shields or goggles recommended.

Skin Protection

Chemical-resistant gloves.

Respiratory Protection

The level of respiratory protection needed should be based on the required protection factor after evaluating chemical exposures using appropriate industrial hygiene monitoring and/or OSHA guidance.

9. Physical And Chemical Properties

No Data Available...

MATERIAL SAFETY DATA SHEET**Leisure Time Renew Tabs****9. Physical And Chemical Properties - Continued****Appearance**

White tablet

Odor

None

Chemical Type: Mixture

Physical State: Solid

Melting Point: DECOMPOSES °F

Boiling Point: DECOMPOSES °F

Specific Gravity: 1.2

Molecular Weight: PROPRIETARY

Percent Volatiles: NIL

Vapor Pressure: NIL

Vapor Density: NOT VOLATILE

Solubility: >25% AT 20C (68F)

Evaporation Rate: NOT VOLATILE

Corrosive, Oxidizer

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability)

The mixture of this product with compounds containing halides or active halogens (bromine, chlorine, iodine) can cause the release of the respective halogen gas, if moisture is present. Avoid these gases (bromine and chlorine) because they are very irritating to eyes and lungs even at low concentrations. Never mix concentrated product with dry or concentrated bromine containing chemicals, such as bromates, bromides, or any concentrated bromine pool chemicals. Mixing this product with dry or concentrated chlorine containing chemicals, such as hypochlorites, sodium dichloroisocyanurate, sodium trisocyanurate or with sodium chloride, may cause the release of chlorine gas.

Mixing with cyanides can cause release of hydrogen cyanide gas. Mixing with heavy metal salts such as those of cobalt, nickel, copper, or manganese can cause decomposition with release of oxygen and heat.

Incompatible Materials

Alkalis, Heavy Metals cause evolution of Oxygen gas. Halogens and cyanides can cause release of gases of these compounds.

Hazardous Decomposition Products

Oxygen

11. Toxicological Information**Acute Studies**

This product is a severe skin and eye irritant, but is not a skin sensitizer in animals.

12. Ecological Information

No Data Available...

13. Disposal Considerations




Dispose in accordance with applicable federal, state and local government regulations.

14. Transport Information

No Data Available...

MATERIAL SAFETY DATA SHEET

Leisure Time Renew Tabs

14. Transport Information - Continued									
<u>Proper Shipping Name</u> CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S. (Monopersulfate Compound)									
<u>Hazard Class</u> 8, PGII (<=1kg Consumer Commodity ORM-D)									
<u>DOT Identification Number</u> UN3260									
<u>DOT (Pictograms)</u> 									
15. Regulatory Information									
<u>SARA Hazard Classes</u> Acute Health Hazard									
<u>Canadian Regulatory Information</u> Class D, Div 2b - Toxic Material. Skin or Eye Irritant Class E - Corrosive Material Class C - Oxidizing Material									
<u>WHMIS - Canada (Pictograms)</u> 									
NFPA	HMIS								
	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="background-color: #00b0f0; color: white;">HEALTH</td> <td style="text-align: center;">3</td> </tr> <tr> <td style="background-color: #ff0000; color: white;">FLAMMABILITY</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="background-color: #ffff00;">REACTIVITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td>PERSONAL PROTECTION</td> <td style="text-align: center;">E</td> </tr> </table>	HEALTH	3	FLAMMABILITY	0	REACTIVITY	1	PERSONAL PROTECTION	E
HEALTH	3								
FLAMMABILITY	0								
REACTIVITY	1								
PERSONAL PROTECTION	E								
16. Other Information									
<u>Revision/Preparer Information</u> MSDS Preparer: JHW This MSDS Superceeds A Previous MSDS Dated: 10/13/2003									
<u>Disclaimer</u> Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s). Leisure Time									