

MATERIAL SAFETY DATA SHEET

Page 1 of 5

Leisure Time Floating Brominator

4. Deschart And Osmanna Islandifisation				
1. Product And Company Identification Supplier Leisure Time 1400 Bluegrass Lakes Parkway Alpharetta, GA 30004 United States Telephone Number: (770) 521-5999 FAX Number: (770) 521-5959 Web Site: www.poolspacare.com	Manufacturer Advantis Technologies, Inc. 1400 Bluegrass Lakes Parkway Alpharetta, GA 30004 United States Telephone Number: (770) 521-5999 FAX Number: (770) 521-5959 Web Site: www.poolspacare.com			
Supplier Emergency Contacts & Phone Number CHEMTREC - DAY OR NIGHT: (800) 424-9300	Manufacturer Emergency Contacts & Phone Number CHEMTREC - DAY OR NIGHT: (800) 424-9300			
Issue Date: 08/05/2004 Product Name: Leisure Time Floating Brominator Chemical Name: Bromine Tablets BCDMH Chemical Family: Brominating disinfecting tablets, Active Halogen Chemical Formula: BrCl(CH3)2 C3N2O2 MSDS Number: 50				
2. Composition/Information On Ingredients				
Ingredient Name		CAS Number	Percent Of TotalWeight	
1,3 DICHLORO-5, 5-DIMETHYL-HYDANTOIN		118-52-5	rotal Weight	
1,3 DICHLORO-5, ETHYL-5-METHYL HYDANTOIN		89415-87-2		
1-BROMO-3-CHLORO-5, 5-DIMETHYLHYDANTOIN		16079-88-2		
SODIUMCHLORIDE		7647-14-5		
Ingredients listed in this section have been determined to be hazardous as defined in 29CFR 1910.1200. Materials determined to be health hazards are listed if they comprise 1% or more of the composition. Materials identified as carcinogens are listed if they comprise 0.1% or more of the composition. Information on proprietary materials is available in 29CFR 1910.1200(i)(1).				
Hazards Identification (Pictograms)				
3. Hazards Identification				
<u>Primary Routes(s) Of Entry</u> Skin Contact, Inhalation <u>Eye Hazards</u> Causes irreversible eye damage.				
Skin Hazards May cause severe skin irritation.				
Ingestion Hazards				

Aspiration hazard if swallowed. Can enter lungs and cause damage.

MATERIAL SAFETY DATA SHEET

Leisure Time Floating Brominator

3. Hazards Identification - Continued

Inhalation Hazards

Causes severe respiratory tract irritation.

Signs And Symptoms

Irritation of Skin, Eyes and Respiratory Passages

Conditions Aggravated By Exposure None Known

First Aid (Pictograms)



4. First Aid Measures

<u>Eye</u>

Flush eyes with large amounts of running water for at least 15 minutes. Hold eyelids apart to ensure rinsing of the entire surface of the eye and lids with water. Get medical attention. If physician not available, flush for additional 15 minutes and then transport victim to medical care.

<u>Skin</u>

Immediately wipe away excess material with a dry cloth while removing contaminated clothing and shoes. Under safety shower, wash affected areas thoroughly with large amounts of water, and soap if available, for at least 15 minutes. Get immediate medical attention. Discard or decontaminate clothing and shoes.

Ingestion

If swallowed, immediately give 3-4 glasses of water. DO NOT INDUCE VOMITING. If vomiting occurs, give fluids again. Get immediate medical attention. Have physician determine if patient's condition allows induction of vomiting or evacuation of stomach. Do not give anything by mouth to an unconscious or convulsing person.

Inhalation

Remove from area to fresh air. If not breathing, clear airway and start artificial respiration. If victim is having trouble breathing, give supplemental oxygen, if available. Get immediate medical attention.

Fire Fighting (Pictograms)



5. Fire Fighting Measures

Flash Point: n/a °F Flammability Class: Not Flammable

Fire And Explosion Hazards

Material is combustable in a fire and produces gases of hydrogen bromide, bromine gas-nirtogen oxides, and hydrogen chloride.

Extinguishing Media

Use CO2 (Carbon Dioxide), dry chemical, or water spray

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear.

6. Accidental Release Measures

Clean up spill immediately. Carefully sweep up material and place in a compatable container for reclamation. Use appropriate containers to avoid environmental contamination.

MATERIAL SAFETY DATA SHEET

Leisure Time Floating Brominator

7. Handling And Storage Handling And Storage Precautions Keep out of reach of children. Store material in a cool and dry place away from oxidizers. Use only with adequate ventilation. Avoid breathing dust. Handling Precautions Avoid breathing dust or vapor. Avoid contact with skin and clothing. Avoid contact with eyes. Avoid creating dust. Long sleeves and pants required to prevent prolonged or repeated skin contact. Storage Precautions Do not reuse container. Store in a cool dry place. Store away from Oxidizing agents. Work/Hygienic Practices Use safe chemical handling procedures suitable for the hazards presended by this material. Protective Clothing (Pictograms) 8. Exposure Controls/Personal Protection Engineering Controls Use with adequate general and local exhaust ventilation. Eye/Face Protection Safety glasses with side shields or goggles. Skin Protection Chemical-resistant gloves. **Respiratory Protection** General room ventilation is normally adequate. The level of respiratory protection needed should be based on the required protection factor after evaluating chemical exposures using appropriate industrial hygiene monitoring and/or OSHA guidance. 9. Physical And Chemical Properties Appearance White tablet Odor Halogen Chemical Type: Mixture Physical State: Solid Melting Point: DECOMPOSES °F Boiling Point: n/a °F Specific Gravity: 1.8-2.0 Molecular Weight: NOT DETERMINED Percent Volitales: NOT DETERMINED Vapor Pressure: NOT APPLICABLE Vapor Density: NOT VOLATILE Solubility: 0.2% @ 25C Evaporation Rate: n/a **10. Stability And Reactivity** Stability: STABLE Hazardous Polymerization: WILL NOT OCCUR

MATERIAL SAFETY DATA SHEET

Leisure Time Floating Brominator

10. Stability And Reactivity - Continued
Incompatible Materials
Acids/Bases and Oxidizers/Reducing agents Organic chemicals
Hazardous Decomposition Products Bromine gas, Hydrogen Bromide, Hydrogen Chloride
11. Toxicological Information
Eye Effects eye irritation (rabbit) : Severe irritant and corrosive
Skin Effects skin irritation (rabbit - Draize test) : Corrosive to both abraded and unabraded skin skin corrosivity (rabbit - US DOT test) : Not corrosive
Acute Oral Effects oral LD50 (rat) : 468-477 mg/kg
Acute Inhalation Effects LC50 mg/kg Rat 0.53 mg/L
Chronic/Carcinogenicity Direct skin and/or eye contact can result in severe skin and eye irritation that may produce irreversable damage. Inhalation can cause severe irritation of nose, throat, and lungs
12. Ecological Information
Acute Toxicity - Fish And Invertebrates LC50 (rainbow trout - 96 hours) : 0.5 mg/L LC50 (bluegill sunfish - 96 hours) : 1.2 mg/L LC50 (Daphnia magna - 48 hours) : 0.4 mg/L LC50 (mysid shrimp - 96 hours) : 0.93 mg/L LC50 (sheepshead minnow - 96 hours) : 1.4 mg/L (as Br2) LC50 (eastern oysters - 96 hours) : 0.84 mg/L (as Br2)
13. Disposal Considerations
Refer to applicable local, state and federal regulations as well as industry standards.
14. Transport Information
Proper Shipping Name OXIDIZING SOLID, N.O.S. (BROMO CHLORO-5, 5-DIMETHYLHYDANTOIN)
<u>Hazard Class</u> 5.1, PGII (<= 1kg Consumer Commodity ORM-D)
DOT Identification Number UN1479
DOT (Pictograms)
15. Regulatory Information
Canadian Regulatory Information
Class C - Oxidizing Material Class D, Div 2b - Poisonous or Infectious Material: other toxic effects,

MATERIAL SAFETY DATA SHEET

Leisure Time Floating Brominator

WHMIS - Canada (Pictograms)
NFPA	HMIS
	HEALTH 3
	FLAMMABILITY 1
	REACTIVITY 1
	PERSONAL PROTECTION B
16. Other Informati	ion
<u>Revision/Preparer</u> MSDS Preparer: J This MSDS Superc	
Disclaimer	
and make no re and assume no or for the conse	nable care has been taken in the preparation of this document, we extend no warranties epresentations as to the accuracy or completeness of the information contained therein, responsibility regarding the suitablility of this information for the user's intended purposes equences of its use. Each individual should make a determination as to the suitability of for their particular purposes(s).
Leisure Time	

Printed Using MSDS Generator™ 2000